

TX No. 2.7.0
(Cancels TX No. 2.6.0)

ENERGY TRANSFER GC NGL PIPELINES LP
JUSTICE PIPELINE
PIPELINE SERVICE TARIFF
APPLYING TO
THE INTRASTATE TRANSPORTATION WITHIN THE STATE OF TEXAS
OF
NATURAL GAS LIQUIDS
TRANSPORTED BY PIPELINE
FROM
POINTS IN TEXAS
TO
POINTS IN TEXAS

The rates published in this tariff are subject to the rules and regulations published in Energy Transfer GC NGL Pipelines LP's Texas Tariff No. 1.0.0, supplements thereto, and successive issues thereof, unless otherwise noted herein. Defined terms not otherwise defined herein shall have meanings given to such terms in such rules and regulations.

EFFECTIVE: JULY 1, 2026

Issued by:
Ryan Kennedy
Director – Commercial Operations
Energy Transfer GC NGL Pipelines LP
1300 Main Street
Houston, Texas 77002
Phone: (713) 989-7000
Fax: (713) 989-1201

Compiled by:
Diane A. Daniels
on behalf of
Energy Transfer GC NGL Pipelines LP
1300 Main Street
Houston, Texas 77002
(713) 989-7425
tariffs@energytransfer.com

Operated under Energy Transfer Company's P5 ID 254879 and T-4 Permit Nos. 06792 & 08505.

Item 10 Rates

The rates published in this tariff are for the intrastate injection and transportation of Y-Grade through the Y-Grade pipeline system of Energy Transfer GC NGL Pipelines LP (Carrier), in accordance with the Y-Grade Specifications set forth in Item 30 below. The rates will be charged based on the volume of Y-Grade delivered to Shipper or Shipper's Consignee at the Delivery Points.

| Tariff Reference | From (Receipt Points) | To (Delivery Points) | Rate (Price per Barrel) |
|-------------------------|---|---|------------------------------------|
| 10-A | Liberty Pipeline Group, LLC – Justice Pipeline Interconnect, Wharton County, Texas | Chevron Phillips Chemical Company LLC Sweeny Chemical & NGL Fractionation Facility, Old Ocean, Brazoria County, Texas (“CPChem Sweeny”) | [I] \$4.7766 |
| 10-B | Liberty Pipeline Group, LLC – Justice Pipeline Interconnect, Wharton County, Texas | Mont Belvieu, Chambers County, Texas Delivery Points | [I] \$4.7766 |
| 10-C | Jackson Plant, Jackson County, Texas | CPChem Sweeny | [I] \$4.7766 |
| 10-D | Jackson Plant, Jackson County, Texas | Mont Belvieu, Chambers County, Texas Delivery Points | [I] \$4.7766 |

Item 20 Commencement of Service

- (a) The pipeline segments necessary to provide the service referenced at Items 10-B, 10-C and 10-D above, which each require receipt capabilities at the Jackson Plant, Jackson County, and/or delivery capabilities in Mont Belvieu, Texas, (“Jackson & Mont Belvieu Service”) are not yet fully constructed and operational as of the effective date of this Tariff. As such, Jackson & Mont Belvieu Service will not be available under this tariff until construction is complete on such segments and they are fully operational. Carrier currently estimates that such service will commence during November or December 2012, but such estimate is subject to many factors and contingencies, many of which are beyond the control of Carrier. Therefore, Carrier can make no assurances or representations whatsoever regarding the date the Jackson & Mont Belvieu Service can be provided under this tariff.
- (b) Because of the period of time until project completion and uncertainties that could impact the completion of the pipeline, Carrier reserves the right to modify or amend this tariff to increase or decrease the rates, or to change other terms and conditions, as appropriate.

Item 30 Y-Grade Product Specifications

The Y-Grade that Carrier will accept for transport shall be a mixture of constituents or component products of NGL composed principally of ethane, propane, butane and natural gasolines, meeting the following Product Specifications:

| Characteristic | Product Specifications | Test Method |
|--|---|----------------------------------|
| Composition: Methane, maximum Aromatics, maximum Olefins, maximum | See Note 1 1.0 wt. % (See Note 2) 1.0 L.V.% | GPA 2177 GPA 2186 GPA 2186 |
| Carbon Dioxide: PPM by Volume in Liquid | 500 max. | GPA 2177 |
| Vapor Pressure: At 100°F psig | 600 max. | ASTM D-6378 |
| Corrosiveness: Copper strip at 100°F | No. 1 | ASTM D-1838 |
| Volatile Sulfur: PPM by weight, maximum | 1200 | ASTM D-2784 |
| Hydrogen Sulfide: Pass/Fail | Pass | ASTM D-2420 |
| Distillation: End point 14.7 psia, °F, maximum See Note 3 | 375.0° | ASTM D-7344 |
| Color: Saybolt Number, minimum See Note 3 | +25.0 | ASTM D-6045 |
| Existing Gum: Washed Unwashed See Note 4 | <=1mg/100ml <=1mg/100ml | ASTM D-381 |
| Dryness: Free Water, @ 34°F | None | Inspection |
| Product Temperature: Degrees Fahrenheit Minimum Maximum | 60° 100° | |
| Contaminants: See Note 4 | | |

Note 1: Methane: lesser of 0.5 liquids volume percent (L.V.%) of the total stream or 1.5 L.V.% of the ethane content. For accounting purposes, a maximum of 1.5 L.V.% methane in the ethane will be considered ethane. Any excess above this specification shall not be accounted for.

Note 2: Or 10 L.V.% maximum in contained natural gasoline

Note 3: Distillation and Color to be run on that portion of the mixture having a boiling point of 70 degrees and above at atmospheric pressure.

Note 4: The Y-Grade shall be commercially free from sand, dust, gums, gum-producing substances, oil, glycol, inhibitors, amine, any other contaminants, or any compound added to the product to enhance the ability to meet these specifications.

**The aforementioned specifications may be modified from time to time by Carrier in its sole discretion.

Explanation of Reference Marks

[I] Increased